

MULTIMETERS & VOLTAGE TESTERS

RECEPTACLE TESTER WITH GFCI

- Tests whether the outlet is properly wired
- Can perform the entire array of tests by simply plugging the device into the outlet
- Easy to read light pattern chart
- Detects most common 3-wire receptacle issues
- LED indicators identify 5 wiring faults
- Status indicator chart
- GFCI trip test
- Voltage: 110 - 125V AC
- Frequency Range: 50 - 60Hz
- Maximum Current: 15 A
- Certification(s): CE, UL



REED

Model No.	Mfg. No.	Description	Price /Each
IC455	R5210	Receptacle Tester	

CONTINUITY TESTER

- Lightweight design connects with alligator clips and the instrument suspends from cable
- Local and remote continuity tester
- Probe flashes green or red to indicate polarity
- Display Type: Indicator Light
- Wire Verification Distance: 10000 feet (3000 meters)
- Minimum Wire Size: 26 gauge
- Power Supply: 9 V Battery
- Visual Indicator: Yes (green and red LEDs)
- Audible Indicator: Yes (Pulsating Beeper, approx. 85 dB)
- Fuse: 0.5A/250V
- Operating Temperature: 14 to 113°F (-10 to 45°C)



REED

Model No.	Mfg. No.	Description	Price /Each
IB868	R5300	Continuity Tester	

TRUE RMS DIGITAL MULTIMETER

- Measures AC/DC voltage and current, frequency, resistance, capacitance and temperature
- Built-in non-contact voltage detector and double molded plastic housing
- Diode check and continuity functions
- Relative and data hold functions
- Backlit LCD and low battery indicator
- Cat. III 600V safety rating
- Voltage Readings: AC/DC
- Current Readings: AC/DC
- Range Selection: Autoranging/Manual
- Display: 6,000 count LCD display
- Continuity Check: Audible signal if resistance $\leq 10\Omega$
- Duty Cycle: Yes (0.1-99.9%)
- Auto Power Off: Yes (after 15 minutes)
- Power Supply: 2 x AA batteries
- Overvoltage Category: CAT. III 600V
- Product Certification: CE



REED

Model No.	Mfg. No.	Description	Price/Each
IB825	R5007	Multimeter	

COMPACT MULTIMETER WITH NON-CONTACT VOLTAGE

- Measures AC/DC voltage and current, resistance, capacitance, frequency, diode and continuity
- Built-in non-contact voltage detector and double molded plastic housing
- 4,000-count backlit LCD display
- Low battery indicator and auto shut-off
- CAT III 600V safety rating
- Includes: Multimeter with NCV, Test leads, Batteries
- Voltage Readings: AC/DC
- Current Readings: AC/DC
- AC Voltage Range: 4, 40, 400, 600V
- DC Voltage Range: 400mV, 4, 40, 400, 600V
- AC/DC Current Range: 400 μ A, 4, 40, 400mA
- Resistance Range: 400 Ω , 4, 40, 400k Ω , 6, 40M Ω
- Capacitance Range: 50, 500nF, 5, 50, 100 μ F
- Frequency Range: 9.999Hz to 60kHz
- Product Certifications: CE
- Operating Temperature: 32 to 104°F (0 to 40°C)
- Dimensions: 4.4 x 2.3 x 1.4" (112 x 58 x 35mm)



REED

Model No.	Mfg. No.	Description	Price/Each
IC695	R5099	Multimeter	

MILLI-OHMMETER

- 4 terminal input for high accuracy of low resistance
- LSI circuitry provides high accuracy, reliability and durability
- Built-in overload protection
- Large LCD display
- Dimensions: 6-5/16" x 4-11/16" x 3-5/16"



REED

Model No.	Mfg. No.	Measuring Range	Max. Current Output mA	Price /Each
HM645	K5090	0.1 - 2000 m Ω	100	

DIGITAL MULTIMETERS

- True RMS AC/DC voltage and current measurements
- 0.05 % basic DC accuracy
- 40 000-count resolution
- Measures frequency, capacitance and temperature
- Diode check and continuity test
- Backlit LCD readout with analog bar graph
- 1000 V input protection on all ranges
- 4-20 mA process loop measurements with % readout
- Data hold, Max/Min recording mode
- Peak capture mode
- IP67 dust and waterproof
- EN61010-1 Cat. IV 600 V, Cat. III 1000 V safety rating
- Includes test leads and 9 V battery

SPECIFICATIONS:

AC/DC Voltage Range:	1000 V
Accuracy:	AC: $\pm 1.0\%$; DC: $\pm 0.05\%$
AC/DC Current Range:	10 A
Accuracy:	AC: $\pm 1.5\%$; DC: $\pm 1.0\%$
Resistance Range:	40 M Ω
Accuracy:	$\pm 0.3\%$
Frequency Range:	10 MHz
Accuracy:	$\pm 0.1\%$
Capacitance Range:	40 mF
Accuracy:	$\pm 3.5\%$
Duty Cycle Range:	99.9%
Accuracy:	$\pm 1.2\%$
Temperature Range:	760°C (1400°F)
Accuracy:	$\pm 1.0\%$
Dimensions:	182 x 82 x 55 mm
Weight:	360 g

XC308



REED

Model No.	Mfg. No.	Description	Price/Each
XC308	R5010	Digital Multimeter	
IA707	FC-300	Fused Test Lead Sets	
IA184	CP-09	Ac Current Clamp-On Adapters	
HN413	CA-52A	Carrying Case	